



FEATURES ———

- Overlapping double-door with 3-point latch and stainless steel lift-off hinges
- Stainless steel handle with padlock provisions
- Door stop
- Window-type or bar-type current transformer
- Removable copper bus links
- Neutral pad with mechanical lugs
- Dual rated (Cu/Al) 750MCM mechanical lugs
- Drip-shield top and seam-free sides
- No gasketing or knockouts
- Removable gland plate
- Ground stud provided, 1/2 in. diameter



UTILITY TRANSFORMER METERING CABINET

1600-2000 AMP, 600VAC, TYPE 3R

APPLICATION

Lake Shore Electric's Duke Energy approved utility transformer metering cabinet provides Type 3R protection and includes factory installed bus for utility provided 1600-2000 amp metering equipment.

Industry Standard: UL 414 Listed; Type 3R File No. E240038



PRODUCT SPECIFICATION

Utility Co).	Installation	Electrical Specifications	Dimensions (H x W x D)	Lb	Lug	Size
			Pad Mount 1600-2000 Amp, 50kAIC, 600V 84 x 52 x 2		785	Line	Load
Duke Ene	iergy	Pad Mount		84 x 52 x 24		(8) 1/0 - 750MCM Per Phase & Neutral	(8) 1/0 - 750MCM Per Phase & Neutral

UTMC MODEL CODES -

Model	Finish	Enclosure Material
UTMC-HD-845224-20M-3A-DUK-00	Gray Polyester Powder Coat; G90 Equivalent Protection	Hot Rolled Steel
UTMC-HD-845224-20M-3B-DUK-00	Mill Finish	Aluminum
UTMC-HD-845224-20M-3C-DUK-00	#4 Brushed Finish	304 Stainless Steel
UTMC-HD-845224-20M-3D-DUK-00	#4 Brushed Finish	316 Stainless Steel

Iseenclosure.com/utmc











UTILITY TRANSFORMER METERING CABINET 1600-2000 AMP, 600VAC, TYPE 3R





Iseenclosure.com/utmc





